



# MATERIAL SAFETY DATA SHEET

Product Name: XYPEX MEGAMIX II

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

---

**Product Name:** XYPEX MEGAMIX II  
**Recommended use:** Repair and protection of concrete.  
**Company Name:** Concrete Waterproofing Manufacturing Pty. Ltd,  
T/A Xypex Australia (ABN 96 093 161 963)  
**Address:** 45 Union Road, Post Office Box 255, LAVINGTON  
NSW 2641  
**Emergency Tel.** 02 60402444 A/h 0419 202 995

---

## 2. HAZARD IDENTIFICATION

---

Classified as hazardous according to the NOHSC criteria  
Not classified as a dangerous goods by the criteria of the ADG Code

**Risk Phrases:** R/36,37,38 Irritating to eyes, respiratory system and skin  
R/41 Risk of serious damage to eyes.  
R/43 May cause sensitisation by skin contact.

**Safety Phrases:** S/22 Do not breathe dust.  
S/24/25 Avoid contact with the skin and eyes.  
S/26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37/S39 Wear suitable gloves and eye / face protection.

---

## 3. COMPOSITION /INFORMATION ON INGREDIENTS

---

<b>Ingredients:</b>	<b><u>Name</u></b>	<b><u>CAS</u></b>	<b><u>Proportion</u></b>
	Portland cement	65997-15-1	20-40%
	Alkaline Earth Compound	1317-65-3	20-40%
	Silica Sand (graded)	14808-60-7	30-70%
	Other ingredients not determined to be hazardous		Balance

---

## 4. FIRST AID MEASURES

---

**Eye contact:** Quickly and gently blot or brush away any dry powder  
Irrigate with large amounts of water for at least 15-20 minutes.  
Seek immediate medical attention.

**Skin Contact:** Continuously flush contaminated area with lukewarm, gently flowing water for at least 15-20 minutes. Remove contaminated clothing and wash before reuse or discard. If symptoms develop seek immediate medical attention.

**Inhalation:** Remove person to fresh air and seek immediate medical attention.

**Oral ingestion:** Wash out mouth with water and drink 1 cup (240-300ml) of water followed by dilution with milk if available. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing. Seek immediate medical attention.

---

## 5. FIRE FIGHTING MEASURES

---

<b>Extinguishing Media:</b>	Not applicable - Product is non-combustible.
<b>Specific Hazards:</b>	In contact with extinguishing water, an alkaline solution is produced which can cause irritation.
<b>Precautions for Fire-Fighters:</b>	Fire fighters should wear full protective clothing and self contained breathing apparatus.
<b>Hazchem Code:</b>	Not applicable.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

<b>Emergency Procedures:</b>	Prevent spillage from entering storm water and sewer drains.
<b>Methods and materials for containment and clean up:</b>	Use dry clean up procedures and avoid generating dust. Increase ventilation and wear full protective clothing and sufficient respiratory protection. Vacuum device or shovel suitable for clean up. Place waste material in plastic or metal drums with tightly sealed lids for disposal.

---

## 7. HANDLING AND STORAGE

---

<b>Handling:</b>	Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in well ventilated area and avoid contact with incompatible materials.
<b>Storage:</b>	Product should be stored in dry, moderate environment, and protected from water or cold damage. Store away from foodstuff containers. Keep in sealed containers until product is required.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

<b>Exposure standards:</b>	TWA 10 mg/m <sup>3</sup> Portland Cement Total Dust TLV – TWA 5 mg/m <sup>3</sup> Alkaline Earth Compound TLV – TWA 0.1mg/m <sup>3</sup> (respirable) Recommendation: Keep exposure to dust as low as practicable, respirable crystalline silica should be kept below 0.1mg/m <sup>3</sup> TWA.
<b>Other information relating to exposure:</b>	Cement products may contain crystalline silica as an impurity. Worksafe Australia has yet to classify crystalline silica as a human carcinogen. Repeated exposed to respirable crystalline silica dust may lead to silicosis, a serious lung disease. The onset of silicosis is usually slow and lung damage may occur even when no symptoms or signs of ill health have occurred. Exposure to respirable crystalline silica dust contained in the product must be prevented to avoid risk of lung disease.
<b>Eng. Controls: Personal Protective</b>	Use in well ventilated areas. Maintain air concentrations below exposure standards. It is recommended that the user wear rubber gloves, a class P1 or P2 particulate respirator or equivalent dust mask, fitted correctly, tight fitting safety goggles, and impervious full length clothing that protects the skin from contact. Additional safety precautions may include, eyewash station, shower facility, and ventilation sufficient in volume and distribution to maintain dust exposure below the 10 mg/m <sup>3</sup> level.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Physical State:</b>	Solid
<b>Odour and appearance:</b>	Odourless grey colour
<b>PH Value</b>	10-13
<b>Specific Gravity</b>	2.8 –3.0
<b>Boiling/melting point:</b>	>1200°C
<b>Vapour pressure:</b>	Not applicable
<b>Vapour density:</b>	Not applicable
<b>Solubility:</b>	2.0g/L
<b>VOC Content:</b>	None
<b>Flash Point:</b>	Not applicable
<b>Flammability</b>	Not applicable
<b>Other properties</b>	Non explosive

---

## 10. STABILITY AND REACTIVITY

---

<b>Chemical Stability:</b>	Products are chemically stable.
<b>Conditions to avoid:</b>	Protect from water and cold damage.
<b>Incompatible materials:</b>	Products are incompatible with strong acids.
<b>Hazardous decomposition:</b>	Products will not decompose into hazardous by-products and it will not polymerise.
<b>Hazardous reactions:</b>	Contact with water should be avoided. Wet Portland cement is alkaline.

---

## 11. TOXICOLOGICAL INFORMATION

---

**Toxicology Information:** No toxicity data is available for these specific products

**Effects of Acute(short term) exposure to products:**

Ingredients in the products are dermal irritants and dermatitis may develop following exposure. Ingredients may also irritate or cause burning sensation to eyes, nose and throat and may cause abdominal discomfort. Eye burns can result from exposure and may cause permanent corneal damage.

**Effects of Chronic (long term) exposure to products:**

Exposure to dust can cause perforation of the nasal septum. Prolonged exposure to ingredients in these products can cause lung and respiratory damage. Portland cement and Alkaline earth compound are corrosive to the skin, chromium sensitisation may cause development of allergic dermatitis. Excess inhalation of crystalline silica dust may result in respiratory disease, including Silicosis, pneumoconiosis and pulmonary fibrosis. Studies have shown that smoking increases the risk of silicosis and other lung disease including lung cancer in persons exposed to crystalline silica.

---

## 12. ECOLOGICAL INFORMATION

---

<b>Environ. Protection:</b>	Not expected to create environmental hazard unless dumped in massive quantities.
<b>Mobility:</b>	Not available
<b>Persistence/</b>	
<b>Degradability:</b>	Not available
<b>Mobility:</b>	Not available
<b>Ecotoxicity:</b>	Not available

---

### 13. DISPOSAL CONSIDERATIONS

---

**Disposal Procedures:** Can be disposed of as common waste. Disposal should be in accordance with local, state and federal regulations.

**Special precautions**

**For landfill and**

**Incineration:** Non required

---

### 14. TRANSPORT INFORMATION

---

**UN Number:** Not classified as Dangerous Goods according to the Australian Code for the transport of Dangerous Goods by Road and Rail.

**UN Proper shipping name:** Non allocated

**Class and subsidiary risk:** Non allocated

**Packing Group:** Not applicable

**Special precautions for user:** Not applicable

**Hazchem Code:** No restrictions known for transport procedures.

**Hazchem Code:** None allocated

---

### 15. REGULATORY INFORMATION

---

**Poisons schedule:** None allocated

**Hazard Category:** Irritant

---

### 16. OTHER INFORMATION

---

MSDS prepared by the Technical Services Department : September 2004.

Revised: March 2009.

The information in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information given is based on technical data that we believe to be reliable at the time of issuing the MSDS. Because conditions of use are outside our control, it is the responsibility of the user to verify safety data for combinations with other materials, or for the use in specific processes, and to verify waste disposal requirements.