

Xypex Australia Attn: Greg Baker PO Box 255 Lavington NSW 2641 AUSTRALIA

22/06/2012

Dear Greg,

Please find the attached report to AS/NZS 4020:2005 for M P&P Mortar submitted for testing.

Should you have any enquiries about the report or any other matters pertaining to the Standard please contact the laboratory on 61 8 7424 1512

Yours sincerely,

Michael Glasson

Product Testing Team Leader

M Marion.



PO Box 1751 Adelaide SA 5001 250 Victoria Square Adelaide SA 5000 Tel: 1300 653 366 Fax: 1300 883 171

Internet: www.awqc.com.au Email: awqc@sawater.com.au



FINAL REPORT

Report ID: 104792

Report Information

Submitting Organisation: 00109093 : Xypex Australia **Account**: 130086 : Xypex Australia

AWQC Reference: 130086-2011-CSR-8: Prod Test: MP & P Mortar

Project Reference: PT-1793

Product Designation: M P&P Mortar

Composition of Product: Portland Cement and Alkaline Earth Compounds (see attached Product Data Sheet and

MSDS).

Product Manufacturer: Concrete Waterproofing Manufacturing Pty. Ltd., Union Rd, Lavington, NSW.

Use of Product: In-Line/Repair Mortar for Concrete Repairs.

Sample Selection: As provided by the submitting organisation

Testing Requested: AS/NZS 4020:2005 TESTING OF PRODUCTS FOR USE IN CONTACT WITH

DRINKING WATER

Product Type: Composite

Samples: Samples were prepared and controlled as described in Appendix A of AS/NZS

4020:2005

Extracts: Extracts were prepared as described in Appendix C, D, E, F, G, H.

Project Completion Date: 21-Jun-2012

Project Comment : The results presented herein demonstrate compliance of M P&P Mortar to AS/NZS

4020:2005 when exposed at area to volume ratios up to 15000 mm2/L at 20°C ± 2°C.

PLEASE NOTE THAT THIS REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL

THE RESULTS STATED IN THIS REPORT RELATE TO THE SAMPLE OF THE PRODUCT SUBMITTED FOR TESTING. ANY CHANGES IN THE MATERIAL FORMULATION, PROCESS OF MANUFACTURE, THE METHOD OF APPLICATION, OR THE SURFACE AREA-TO-VOLUME RATIO IN THE END USE, COULD AFFECT THE SUITABILITY OF THE PRODUCT FOR USE IN CONTACT WITH DRINKING WATER

M Marion.

Michael Glasson APPROVED SIGNATORY



Australian Water Quality Centre

FINAL REPORT

Report ID: 104792

Summary of Results

APPENDIX	RESULTS		
C — Taste of Water Extract	Passed at an exposure of 15000 mm2 per Litre.		
D — Appearance of Water Extract	Passed at an exposure of 15000 mm2 per Litre.		
E — Growth of Aquatic Micro-organisms	Passed at an exposure of 15000 mm2 per Litre.		
F - Cytotoxic Activity of Water Extract	Passed at an exposure of 15000 mm2 per Litre.		
G - Mutagenic Activity of Water Extract	Passed at an exposure of 15000 mm2 per Litre.		
H — Extraction of Metals	Passed at an exposure of 15000 mm2 per Litre.		

Summary Comment:

Sixteen soakings were performed to obtain a pH < 9.0. In accordance with section A8 (Cementitious Products). Sample mixed and prepared adding 1 part water to 4 parts M P&P Mortar.



PO Box 1751 Adelaide SA 5001 250 Victoria Square Adelaide SA 5000 Tel: 1300 653 366 Fax: 1300 883 171

Internet: www.awqc.com.au Email: awqc@sawater.com.au



FINAL REPORT

Report ID: 104792

CLAUSE 6.2 Taste of Water Extract

Sample Description The sample consisted of two glass slides (single side coated on each) measuring 75 mm x

100 mm providing an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of pre-conditoning water(Al 12.6).

Extraction Temperature 20°C ± 2°C.

Test Method Taste of Water Extract (Appendix C)

Test Information

Scaling Factor Not applied.

Results Not detected.

Evaluation The product passed the requirements of clause 6.2 when tested at an exposure of 15000

mm2 per Litre.

Number of Samples 2.

Test Comment Not applicable.

Peter Christopoulos APPROVED SIGNATORY



Internet: www.awqc.com.au Email: awqc@sawater.com.au



FINAL REPORT

Report ID: 104792

CLAUSE 6.3 Appearance of Water Extract

Sample Description The sample consisted of two glass slides (single side coated on each) measuring 75 mm x

100 mm providing an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of pre-conditoning water(Al 12.6).

Extraction Temperature 20°C ± 2°C.

Test Method Appearance of Water Extract (Appendix D)

Scaling Factor Not applied.

Results

	Test (- Blank)	Maximum Allowed	<u>Units</u>
Colour	<1	5	HU
Turbidity	0.2	0.5	NTU

Evaluation The product passed the requirements of clause 6.3 when tested at an exposure of 15000

mm2 per Litre.

Number of Samples 1.

Test Comment Not applicable.

Joanne Clark APPROVED SIGNATORY



Tel: 1300 653 366 Fax: 1300 883 171

Internet: www.awqc.com.au Email: awqc@sawater.com.au



FINAL REPORT

Report ID: 104792

CLAUSE 6.4 Growth of Aquatic Micro-organisms

Sample Description The sample consisted of two glass slides (single side coated on each) measuring 75 mm x

100 mm providing an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of test water.

Test Method Growth of Aquatic Micro-organisms (Appendix E)

Inoculum The volume of the inoculum was 100 mL

Scaling Factor Not applied.

Results

Mean Dissolved Oxygen Control 7.2 mg/L

Mean Dissolved Oxygen Difference Positive Reference 5.4 mg/L

Negative Reference 0.1 mg/L

Test 0.10 mg/L

Evaluation The product passed the requirements of clause 6.4 when tested at an exposure of 15000

mm2 per Litre.

Number of Samples 1.

Test Comment Not applicable.

Stephanie Semczuk
APPROVED SIGNATORY



Corporate Accreditation No.1115
Chemical and Biological Testing
This document is issued in accordance
with NATA's accreditation requirements.
Accredited for compliance with ISO/IEC 17025

ABN 69336525019

Internet: www.awqc.com.au Email: awqc@sawater.com.au



FINAL REPORT

Report ID: 104792

CLAUSE 6.5 Cytotoxic Activity of Water Extract

Sample Description The sample consisted of two glass slides (single side coated on each) measuring 75 mm x

100 mm providing an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of pre-conditoning water(Al 12.6).

Extraction Temperature 20°C ± 2°C.

Test Method Cytotoxic Activity of Water Extract (Appendix F)

Scaling Factor Not applied.

Results Non cytotoxic.

Evaluation The product passed the requirements of clause 6.5 when tested at an exposure of 15000

mm2 per Litre.

Number of Samples 1.

Test CommentThe test extracts and blank extracts were used to prepare nutrient growth medium and

subsequently used to grow a cell line (ATCC Number CCL 81) in the analysis. In addition

zinc sulphate (0.4 mmol) was used for the positive control in the analysis.

Brendon King APPROVED SIGNATORY





FINAL REPORT

Report ID: 104792

CLAUSE 6.6 Mutagenic Activity of Water Extract

Sample Description The sample consisted of two glass slides (single side coated on each) measuring 75 mm x

100 mm providing an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of pre-conditoning water(Al 12.6).

Extraction Temperature 20°C ± 2°C.

Test Method Mutagenic Activity of Water Extract (Appendix G)

Scaling Factor Not applied.

Results

<u>Bacteria Strain</u> <u>Number of Revertants per Plate</u>

Salmonella typhimurium TA98 Mean ± Standard deviation	S9 -	Blank 33, 48, 33 38.0 ± 8.7	Sample Extract 35, 24, 32 30.3 ± 5.7	Positive Controls 2961, 2898, 2747 2868.7 ± 110.0	<u>NPD (</u> 20μg)
Mean ± Standard deviation	+	39, 37, 35 37.0 ± 2.0	23, 20, 27 23.3 ± 3.5	2914, 2628, 2774 2772.0 ± 143.0	<u>2-AF</u> (20μg)
Salmonella typhimurium TA100 Mean ± Standard deviation	-	258, 287, 347 297.3 ± 45.4	237, 262, 295 264.7 ± 29.1	1086, 971, 988 1015.0 ± 62.1	<u>Azide</u> (1.0μg)
Mean ± Standard deviation	+	311, 274, 279 288.0 ± 20.1	243, 244, 228 238.3 ± 9.0	1807, 2661, 2193 2220.3 ± 427.7	<u>2-AF</u> (20μg)
Salmonella typhimurium TA102 Mean ± Standard deviation	-	327, 304, 367 332.7 ± 31.9	388, 351, 395 378.0 ± 23.6	1684, 2094, 2465 2081.0 ± 390.7	Mitomycin C(10μg)
Mean ± Standard deviation	+	300, 365, 393 352.7 ± 47.7	293, 270, 291 284.7 ± 12.7		

Comments S9 was used as a metabolic activator. NPD (4-nitro-o-phenylenediamine), Azide, and

Mitomycin C are specific positive controls for strains TA98, TA100 and TA102 respectively while 2 - AF (2-aminofluorene) when used in conjunction with S9 is a

positive control for both TA98 and TA100

Evaluation The product passed the requirements of clause 6.6 when tested at an exposure of 15000

mm2 per Litre.

Number of Samples 1.

Test Comment Not applicable.

Peter Christopoulos APPROVED SIGNATORY





FINAL REPORT

Report ID: 104792

CLAUSE 6.7 Extraction of Metals

Sample Description The sample consisted of two glass slides (single side coated on each) measuring 75 mm x

100 mm providing an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of pre-conditoning water(Al 12.6).

Extraction Temperature 20°C ± 2°C.

Test Method Extraction of Metals (Appendix H)

Scaling Factor Not applied.

Method of Analysis All methods used to determine concentrations of metals are based on those described in

the 21st edition of Standard Methods for the Examination of Water and Wastewater published by the APHA, AWWA and WEF (2005). The methods have been adapted for

the instrumentation in use at the Australian Water Quality Centre.

Concentration of the metals described in Table 2 of the AS/NZS 4020:2005 are

determined as follows:

Antimony, Arsenic, Barium, Cadmium, Chromium, Copper, Lead, Mercury, Molybdenum,

Nickel, Selenium and Silver by Inductively Coupled Plasma Mass Spectrometry.

Results	Limit of Reporting	Blank	Test 1	Test 2	Max Allowed
	mg/L	mg/L	mg/L	mg/L	mg/L
Final Extract					
Antimony	0.0005	<0.0005	<0.0005	<0.0005	0.003
Arsenic	0.0003	0.0004	0.0005	0.0004	0.007
Barium	0.0005	0.0356	0.0240	0.0250	0.7
Cadmium	0.0005	0.0001	0.0003	0.0006	0.002
Chromium	0.0001	0.0002	0.0005	0.0004	0.05
Copper	0.0001	0.3530	0.2035	0.1979	2.0
Lead	0.0001	0.0022	0.0016	0.0013	0.01
Mercury	0.00003	0.00006	0.00018	0.00013	0.001
Molybdenum	0.0001	<0.0001	<0.0001	< 0.0001	0.05
Nickel	0.0001	0.0020	0.0014	0.0014	0.02
Selenium	0.0001	<0.0001	< 0.0001	<0.0001	0.01
Silver	0.00003	<0.00003	< 0.00003	<0.00003	0.1

Evaluation The product passed the requirements of clause 6.7 when tested at an exposure of 15000

mm2 per Litre.

Number of Samples 1

Test Comment Not applicable.

Dzung Bui

APPROVED SIGNATORY

